

Besten

Tilting Air Float Table



Productivity

The gridded table top insures that muntin clips can be quickly located into the optimal position for grid alignment.

Safety

The safety interlock ensures that the table won't tilt without vacuum engaged and stops up.

Efficiency

Foot Pedal Operation - control of the float/vacuum feature with foot pedals allows operator to concentrate on assembly duties.

Description & Features

The Tilting Air Float Table is used to transfer glass, allow the placement of muntin assembly and topping assembly of the IGU for productive flexible spacer application.

- Powerful 3 or 5 hp blowers used for ease of glass movement on the table surface.
- Lockable edge stops and pop-up pneumatic alignment stops insure accurate glass registry.
- Table sizes:
 - 60"W x 48" & 60" tilt depths
 - 72"W x 72" tilt depth
 - 84" or 96" W x 60", 72" & 84" tilt depths
 - 108"W x 84" tilt depth

Available Options

- Starburst grid lines available as an add to the standard 5/8"/16mm grid pattern.
- Dual-zone float/vacuum for split mode and efficiency gains.



A division of Truseal Technologies, Inc.

Besten Equipment, Inc.
6680 Parkland Boulevard
Solon, Ohio 44139
216-581-1166 Fax: 216-581-0044
www.besteninc.com

